



# RACORES PARA TUBOS FLEXIBLES TPR



## RACORES RTPR

Art.	d Ø	A	B	C	D Ø	E	G	H	L	Material	Color	Peso g
<b>RTPR 3/8"</b>	G3/8"	14.5	8.5	26	12.0	23.5	6	28	46.5	polipropileno	gris	12
<b>RTPR 1/2"</b>	G1/2"	14.5	9.0	28	15.5	26.5	7	33	50.0	polipropileno	gris	18
<b>RTPR 3/4"</b>	G3/4"	14.0	10.5	35	20.8	26.5	9	38	51.0	polipropileno	gris	26
<b>RTPR 1"</b>	G1"	16.0	9.0	41	26.5	32.5	10	44	57.5	polipropileno	gris	36

Temperatura de trabajo: -10° / +60 °C



## RACORES RTPR

Art.	d Ø	A	B	D Ø	E	H	L	Material	Peso g
<b>RTPR 1" 1/4</b>	G1" 1/4	11	6	34.5	28.5	52	45.5	latón niquelado	340
<b>RTPR 1" 1/2</b>	G1" 1/2	14	7	39.5	34.0	60	55.0	latón niquelado	530
<b>RTPR 2"</b>	G2"	14	7	50.0	33.0	74	54.0	latón niquelado	596

Temperatura de trabajo: -20° / +60 °C